

2014+ Harley-Davidson® M5-800X4 Tuning Guide



Maximum Radio Volume: 3 bars from highest level. Increasing volume past this level will damage your speakers.



Boom!™Box Standard 4.3



Boom!™Box Premium 6.5GT



Boom!™Box Premium GTS



RADIO FLASH REQUIRED
"Rockford Fosgate Tune 2014+ All Models"

REMOTE TURN-ON REQUIRED
use turn-on from brake side

AMPLIFIER TUNING

Before installing amplifier, remove cover and set PRESET to OFF position. Verify remaining settings are properly configured. Replace cover for water-tight protection.

- FRONT INPUT LEVEL:** 12:00 O'Clock
- REAR INPUT LEVEL:** 12:00 O'Clock
- PRESET:** OFF
- PUNCH EQ:** MIN
- CROSSOVER:** HP (High-Pass)
- CROSSOVER FREQ:** 80Hz
- INPUT:** 4CH (4-Inputs)

TEST & SETUP

After system is installed, test for proper operation and adjust radio settings to below configurations.



SPEED VOLUME:
Set AVC (auto volume control) to OFF position.



BASS:
Set to CENTER position.



TREBLE:
Set to CENTER position.



FADER:
Test front/back fader control. Set to DESIRED rider position.



AUDIO ROUTING:
If no audio, check Music/Media is set to speakers, not headphones.

2014+ Harley-Davidson® Factory Amp Bypass Plugs



Boom!™ Audio Stage 1 CVO 4-Speaker

Factory amplifier in fairing. Controls fairing speakers and TourPak.

Bypass Plugs:

- BOOM 1 SYSTEM BYPASS

Boom!™ Audio Stage 2 CVO Ultra 4-Speaker

Factory amplifier in fairing. Controls fairing speakers and TourPak.

Bypass Plugs:

- CVO ULTRA BOOM 1 FAIRING

Boom!™ Audio Stage 2 CVO Road Glide 4-Speaker

Fairing amp controls upper speakers. Left bag amp controls baglid speakers.

Bypass Plugs:

- BOOM 4-SPEAKER FRONT
- BOOM 4-SPEAKER REAR

Boom!™ Audio Stage 2 CVO 6-Speaker

Fairing amp controls upper speakers. Left bag amp controls left lower & baglid speakers. Right bag amp controls right lower & baglid speakers.

Bypass Plugs:

- BOOM 4-SPEAKER FRONT
- CVO AMP BYPASS LEFT SADDLEBAG
- CVO AMP BYPASS RIGHT SADDLEBAG

